

AN 25



OCH ventil, M 5, precisionstyp

Betyg: Inte betygsatt ännu

Pris
Pris 234,89 kr

Pris utan moms 187,91 kr

Rabatt

Momsbelopp 46,98 kr

[Ställ en fråga om denna produkt](#)

Beskrivning

Technical data

Version precision version

Thread M 5

Nominal width [mm] 3.2

flow [l/min] 1.60

Note RoHS-compliant

Weight 27 g / pc.

Further information

GTIN 4050571219420

Customs duty number: 84812090

Description

Materials:

OCH (and) ventiler: AN 25

Body: anodized aluminium, internal parts: aluminium, brass and stainless steel, seals: plastic and NBR

Temperature range:

-10°C to max. +70°C (Standard design: max. +60°C)

Media:

oiled and unoled filtered compressed air

Operating pressure:

-0.95 - 10 bar (Standard design: 2 - 10 bar)

Function:

At outlet A a signal appears only if a signal exists on both inlets at the same time. For different pressures, the lowest pressure will reach outlet A. The UND member has no separate venting as a passive element. After deleting one or both input signals, ventilation occurs via the upstream signal members.

Warning!

An AND-element does not replace a two hand control block!

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.