

1 TF 10



PTFE slang med rostfritt flätat hölje DN 10

Betyg: Inte betygsatt ännu

Pris

Pris 699,64 kr

Pris utan moms 559,71 kr

Rabatt

Momsbelopp 139,93 kr

[Ställ en fråga om denna produkt](#)

Beskrivning

Technical data

DN [mm] 10

Hose Ø inside [mm] 9.75 - 10.30

Hose Ø external [mm] 12.15 - 13.20

PTFE wall thickness [mm] 0.65

Operating pressure [bar] 183

Burst pressure [bar] 552

Min. bend radius [mm] 133

Further information on 1TF10

Weight 160 g / m

GTIN 4050571186715

Customs duty number 39173100

RoHS compliant Yes

Description - PTFE hose with stainless steel braiding DN 10

PTFE slang med rostfritt flätat hölje: 1 TF 10

Materials:

Wire braiding: 1.4306, Inner tube: PTFE

Temperature range:

-60°C bis +220°C

Operating pressure:

at -60°C to max. +120°C: 100% of the table value, above +120°C: minus 1% of the table value for each additional degree of temperature

Tried and tested for usage in:

Food processing, laboratory and medical equipment, vulcanising presses, steam-iron machines as well as cleaning devices, where a high chemical resistance, thermal stability, elasticity and weather resistance are needed.

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.