

1 TF 19



PTFE slang med rostfritt flätat hölje DN 19

Betyg: Inte betygsatt ännu

Pris

Pris 2.067,85 kr

Pris utan moms 1.654,28 kr

Rabatt

Momsbelopp 413,57 kr

[Ställ en fråga om denna produkt](#)

Beskrivning

Technical data

DN [mm] 19

Hose Ø inside [mm] 19.30 - 20.32

Hose Ø external [mm] 22.40 - 23.90

PTFE wall thickness [mm] 1.00

Operating pressure [bar] 103

Burst pressure [bar] 310

Min. bend radius [mm] 203

Further information on 1TF19

Weight 470 g / m

GTIN 4050571186746

Customs duty number 39173100

RoHS compliant Yes

Description - PTFE hose with stainless steel braiding DN 19

PTFE slang med rostfritt flätat hölje: 1 TF 19

Materials:

Wire braiding: 1.4306, Inner tube: PTFE

Temperature range:

-60°C bis +220°C

Operating pressure:

at -60°C to max. +120°C: 100% of the table value, above +120°C: minus 1% of the table value for each additional degree of temperature

Tried and tested for usage in:

Food processing, laboratory and medical equipment, vulcanising presses, steam-iron machines as well as cleaning devices, where a high chemical resistance, thermal stability, elasticity and weather resistance are needed.

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.