FV 014 F



FUTURA för-filter, G 1/4", serie 0, 0,3 my

Betyg: Inte betygsatt ännu
Pris
Pris 1.080,58 kr

Pris utan moms 864,46 kr

Rabatt

Momsbelopp 216,12 kr

Ställ en fråga om denna produkt

Beskrivning

Technical data

Model series Model series 0

Container design with polycarbonate bowl

Condensate drain Semi-automatic

Thread G 1/4"

Container volumes [cm³] 12

Optimal flow* [l/min] 140

H [mm] 132

H1 [mm] 105

L [mm] 43

Mounting brackets W 0 F

Coupling kit KP 0 F

Coupling kit with wall bracket KPW 0 F

Replacement filter V 23/35

För-filter FUTURA: FV 014 F

Input pressure [bar] 1.5 - 12

Further information on FV014F

Weight 125 g / Pcs

GTIN 4050571310523

Customs duty number 84213925

RoHS compliant Yes

Description - FUTURA prefilter, G 1/4", Model series 0

Materials:

Body: PA 66 GF60, seals: NBR, condensate container: polycarbonate

Temperature range:

-10°C bis +50°C

Input pressure:

1.5 - 16 bar (model series 0: 1.5 - 12 bar)

Condensate draining:

Semi-automatic** (activated carbon filter without drainage)

Media:

Compressed air, neutral gases

ATEX:

Operating material without its own potential source of ignition in accordance with Directive 2014/34/EU (not model series 0 or differential pressure indicator / differential pressure gauge)

Advantages:

•simple assembly of single components using coupling kits within a model series.

Application:

Pre-filters are used where high requirements are placed for the purity of compressed air. Fine particles (> 0.3 µm), which can pass unhindered through the sintered filters, are separated here. Pre-filters are also installed in order to increase the service life of microfilters.

Dust removal:

> 0.3 µm (99.99 %)

Optional:

Version with metal bowl and inspection tube (model series 0: without inspection tube) -M, automatic discharge -AM, automatic discharge closed when not pressurised (0 to 16 bar, model series 0: 0 - 12 bar) -AMNC

*at 6 bar input pressure and 0,02 bar pressure loss, **As soon as the input pressure falls below the minimum. input pressure, the drain valve opens automatically. The semi-automatic drain valve can be prevented from opening by screwing the drain screw tight.

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.