# 4 SP 16



4 SP hydraulslang, EN 856, DN 16

Betyg: Inte betygsatt ännu
**Pris**
Pris 888,53 kr

Pris utan moms 710,82 kr

Rabatt

Momsbelopp 177,71 kr

Ställ en fråga om denna produkt

Beskrivning

**Technical data**

DN [mm] 16

Hose Ø inside [mm] 16,0

Hose Ø external [mm] 27,6

Operating pressure [bar] 380

Burst pressure [bar] 1600

Min. bend radius [mm] 140

Size parameter 10

**Further information on 4SP16**

Weight 1,6 kg / m

GTIN 4050571199043

Customs duty number 40092100

RoHS compliant Yes

Description - 4 SP hose, EN 856, DN 16

**Materials**:

Synthetic internal and external rubber

**Temperature range**:

-40? to max. +100?, temporary up to max. + 125?

**Operating range**:

high pressure hydraulic systems

**Resistance**:

Hydraulic oils on basis of mineral oil, air*, water, lubricants and fuels, bio oils

**Delivered as:**

Due to the manufacturing process we cannot exclude that the goods will be supplied in pieces. We attempt to deliver max. 3 pieces, where none of the pieces is shorter than 3 meters.

*hose must be pricked

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.