

4 SP 25



4 SP hydraulslang, EN 856, DN 25

Betyg: Inte betygsatt ännu

Pris

Pris 1.318,91 kr

Pris utan moms 1.055,13 kr

Rabatt

Momsbelopp 263,78 kr

[Ställ en fråga om denna produkt](#)

Beskrivning

Technical data

DN [mm] 25

Hose Ø inside [mm] 25,4

Hose Ø external [mm] 39,0

Operating pressure [bar] 320

Burst pressure [bar] 1400

Min. bend radius [mm] 340

Size parameter 16

Further information on 4SP25

Weight 2 kg / m

GTIN 4050571199067

Customs duty number 40092100

RoHS compliant Yes

Description - 4 SP hose, EN 856, DN 25

4 SP - 4 dubbel stålarmering, EN 856: 4 SP 25

Materials:

Synthetic internal and external rubber

Temperature range:

-40? to max. +100?, temporary up to max. +125?

Operating range:

high pressure hydraulic systems

Resistance:

Hydraulic oils on basis of mineral oil, air*, water, lubricants and fuels, bio oils

Delivered as:

Due to the manufacturing process we cannot exclude that the goods will be supplied in pieces. We attempt to deliver max. 3 pieces, where none of the pieces is shorter than 3 meters.

*hose must be pickled

All data are to be understood as non-binding reference values! We do not assume liability for any data selection not confirmed in writing. Unless otherwise specified, pressure values refer to liquids from Group II at +20°C.